

**Specifications:**

|                         |                                    |
|-------------------------|------------------------------------|
| Sound level Category    | Medium Sound Level                 |
| Mode of Operation       | Slow Pulse                         |
| Mounting                | Panel (see note B)                 |
| Voltage Rating          | 60 to 250 Vac/dc                   |
| Frequency               | 2900 Hz ±500 Hz                    |
| Loudness (Min. Voltage) | 68 dB(A) min. @ 2 FT and 60 Vac/dc |
| Loudness (Max Voltage)  | 78 dB(A) min. @ 2FT and 250 Vac/dc |
| Current Draw            | 4 mA Max @ 60 Vac/dc               |
| Current Draw            | 13 mA Max @ 250 Vac/dc             |
| Min. Pulse Rate (PPS)   | 0.5 @ 60 Vac/dc                    |
| Max. Pulse Rate (PPS)   | 2 @ 250 Vac/dc                     |
| Duty Cycle (%)          | 50 (Approx)                        |
| Storage Temperature     | -40°C to +85°C                     |
| Operating Temperature   | -30°C to +65°C                     |
| Weight (Typical)        | 2.1 oz (60 g)                      |
| Housing                 | 6/6 Nylon, Color Black             |
| Options                 | For other options contact factory  |

**Dimensions:** Inches (mm)

**UL Recognized** 

**RoHS Compliant**

PART DIMENSIONS BEFORE CODE DATE 0824 5 PART DIMENSIONS AFTER CODE DATE 0825 1

